
TM TECHNOLOGIE

# ONTEC G E1E 180 M AT W
# TM-OG.EEATM800W

No: 03A23 | No: 4420/2021 Valid until: 05.09.2026 | No: 88-128652 Valid until: 24.06.2025 | No: B_BK_60112_0425_2024 Valid until: 24.01.2030 | No: 03A23 | No: 2291559.02-UAE Valid until: 05.11.2026 | No: 03A23



| | |
|---|---|
| Producer | **TM Technologie** |
| Category | **emergency luminaires** |
| Application | **evacuation route direction** |
| Family | **ONTEC G** |
| Colour/Colour - RAL | **white , RAL9003** |
| Colour structure | **matte , satin, smooth** |
| Version | **autotest** |
| Operating mode | **M** |
| Duration time | **3 h** |
| Protection degree | **IP20** |
| Impact protection degree | **IK05** |
| Appliance classes | **II** |
| Material | **plastic** |
| Installation method* | **surface, flush-mounted, suspended, wall, ceiling** |
| Adapted to use a pictogram | **yes** |
| Pictogram included | **yes** |
| Pictogram dimensions | **125x125 mm** |
| Evacuation sign dimensions | **250x125 mm** |
| Pictogram type | **foil** |
| Graphic number | **K6** |
| Pictogram logo | **TM Technologie** |
| Luminous flux | **>350 cd/m²** |
| Visibility | **25 m** |
| Colour temperature | **5700 K** |
| Light source | **LED** |
| Maximum light power | **0.9 W** |
| LED lifetime | **50000 h** |
| Minimum temperature | **+10 °C** |
| Maximum temperature | **+35 °C** |
| Battery | **LiFePO4/C 3.2V 1.5Ah** |
| Warranty (body, electronics, light source) | **36 months** |
| Net dimensions **L x W x H** [±2 mm] | **251 mm x 29 mm x 198 mm** |




* Some of mounting methods are possible only with additonal accessory dedicated for that product.