ONTEC S M2 102 M AT W CLD
TM-OS.M2ATM16CW

No: 10A23

No: 4662/2022
Valid until:
02.06.2027

No: 88-139797
Valid until:
24.06.2025

No:
B_BK_60112_0426_2024
Valid until:
24.01.2030

No: 10A23

No: 2291559.02-UAE
Valid until:
05.11.2026

No: 10A23



Producer	**TM Technologie**
Application	**anti-panic lighting**
Family	**ONTEC S**
Colour/Colour - RAL	**white , RAL9003**
Version	**autotest**
Operating mode	**M**
Duration time	**1 h**
Protection degree	**IP65**
Impact protection degree	**IK08**
Appliance classes	**II**
Material	**plastic**
Installation method*	**surface, flush-mounted, suspended, wall, ceiling, at an angle**
Luminous flux emergency	**241 lm**
Light source	**LED**
Maximum light power	**4.7 W**
Active power	**6.5 W**
LED lifetime	**50000 h**
Colour temperature	**5700 K**
Minimum temperature	**-15 °C**
Maximum temperature	**+40 °C**
Battery	**LiFePO4/C 6.4V 1.5Ah**
Warranty (body, electronics, light source)	**36 months**
Net dimensions **L x W x H** [±2 mm]	**272 mm x 40 mm x 144 mm**





* Some of mounting methods are possible only with additonal accessory dedicated for that product.