CERTIFICATE OF COMPLIANCE

Certificate Number	E45172
Report Reference	E45172-19960502
Issue Date	2020-MARCH-19
Issued to:	WAGO Kontakttechnik GmbH & Co. KG Hansastrasse 27 32423 Minden GERMANY
This certificate confirms that representative samples of	COMPONENT - TERMINAL BLOCKS Refer to Addendum Page
	Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.
Standard(s) for Safety:	UL1059 - Terminal Blocks.
Additional Information:	See the UL Online Certifications Directory at https://iq.ulprospector.com for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

CERTIFICATE OF COMPLIANCE

Certificate Number	E45172
Report Reference	E45172-19960502
Issue Date	2020-MARCH-19

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Component terminal blocks, Cat. Nos. 243-204, -208, -211, -212, -214, -215, -304, -308, -314, -504, -508, -514, -614, -705, -706, -707, -708, -720, -721, -722, -723, -724, -725, -726, -727, -728, -729, -804, -808, -814.

Component terminal blocks, Cat. Nos. 243-742, -743, -744, -745, -746, -747, -748, may be followed by suffixes /000-006, /000-007, /000-012.

May be followed by suffixes /010-000.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

File E45172
Project 96ME12203

Issued: May 2, 1996
Revised: June 21, 2023

REPORT

on

TERMINAL BLOCKS

* WAGO GmbH, **& Co. KG**
Minden, Fed. Rep. Germany

Copyright © 1996 Underwriters Laboratories Inc.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce this Report provided it is reproduced in its entirety.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce that portion of this Report consisting of this Cover Page through Page 2.

D E S C R I P T I O N

PRODUCT COVERED:

USR Component terminal blocks, Cat. Nos. 243-204, -208, -211, -212, -214, -215, -304, -308, -314, -504, -508, -514, -614, -705, -706, -707, -708, -720, -721, -722, -723, -724, -725, -726, -727, -728, -729, -804, -808, -814.

USR Component terminal blocks, Cat. Nos. 243-742, -743, -744, -745, -746, -747, -748, may be followed by suffixes /000-006, /000-007, /000-012.

May be followed by suffixes /010-000.

GENERAL CHARACTER AND USE:

The terminal blocks covered by this Report are intended for use in the following Applications and within the ratings specified.

Application -

Commercial appliances (Such as business and EDP equipment, etc.)

General industrial (such as motor controllers, pushbutton stations, etc.)

Terminal Type - Spring Cage Clamp

Type Wiring - Field and Factory wiring applications.

RATINGS:

*Max Voltage - 150 V
Max Current - 7 A
Wire Range - 18-22 AWG, Cu, solid

Product Variations:

243-204 – 4-pole, **dark-grey** housing
243-208 – 8-pole, **dark-grey** housing
243-211 – 8-pole, 4 pole red housing and 4 pole dark-grey housing
243-212 – 8-pole, 4 pole yellow housing and 4 pole light-grey housing
243-214 – 4-pole, **dark-grey** housing, for bus connection
243-215 – 8-pole, 4 pole light-grey housing and 4 pole light-grey housing
243-304 – 4-pole, **light-grey** housing
243-308 – 8-pole, **light-grey** housing
243-314 – 4-pole, **light-grey** housing, for bus connection
243-504 – 4-pole, yellow housing
243-508 – 8-pole, yellow housing
243-514 – 4-pole, yellow housing, for bus connection
243-614 – 4-pole, black housing
243-705 – 8-pole, 4 pole white housing and 4 pole blue housing
243-706 – 8-pole, 4 pole **white** housing and 4 pole orange housing
*243-707 – 8-pole, 4 pole **white** housing and 4 pole **yellowish-green** housing
243-708 – 8-pole, 4 pole light-grey housing and 4 pole dark-grey housing
*243-720 – 4-pole, **yellowish-green** housing
243-721 – 4-pole, grey housing
243-722 – 4-pole, blue housing
243-723 – 4-pole, orange housing
243-724 – 4-pole, light-green housing
243-725 – 4-pole, dark grey housing
243-726 – 4-pole, light grey housing
243-727 – 4-pole, yellow housing
243-728 – 4-pole, **white** housing
243-729 – 4-pole, red housing
243-742 – 2-pole, 4 conductor, **light-green housing***
243-743 – 3-pole, 4 conductor, **light-green housing***
243-744 – 4-pole, 4 conductor, **light-green housing***
243-745 – 5-pole, 4 conductor, **light-green housing***
243-746 – 6-pole, 4 conductor, **light-green housing***
243-747 – 7-pole, 4 conductor, **light-green housing***
243-748 – 8-pole, 4 conductor, **light-green housing***
243-804 – 4-pole, red housing
243-808 – 8-pole, red housing
243-814 - 4-pole, red housing, for bus connection

*** - suffixes /000-006, /000-007, /000-012 may be added to indicate different colour**